

Arris CF

| | |
|------------------------------------|--|
| Video Specifications | |
| Panel Type | 26" Active Matrix (a-si TFT) Advanced Super View LCD ¹ |
| Pixel Resolution | Wide XGA (1366 x 768) |
| Video System | NTSC |
| Brightness | 450 cd/m ² |
| Lamp Life | 60,000 hours ³ |
| Viewing Angles | 170° H / 170° V |
| Audio System | 10W + 10W |
| Tuner Type | Frequency Synthesizer (Analog/Digital) |
| Limited Warranty | 1 year parts and labor |
| Contrast Ratio | 800:1 |
| Aspect Ratio | 16:9 |
| Color Temperature | Selectable: 13000°K, 9500°K, 8000°K, 6500°K, 5000°K (values are approximate) |
| View Modes | Sidebar, Smart Stretch, Stretch, Zoom, Dot by Dot (for PC), Normal (for PC) |
| RS-232 Input | RS-232C x 1 |
| Composite Video Input (A/V) | RCA x 1 |
| Backlight | Fluorescent lamp (Cold Cathode Type) |
| Audio Inputs | RCA L/R x 1 |
| Audio Outputs | RCA L/R x 1 |
| | |
| | ¹ Actual screen size 25 1/2" measured diagonally. |
| | |
| Audio Specifications | |
| | Play MP3 encoded CDs and DVDs. |
| | Waterproof construction and sealed chassis make for no worries in a wet environment. |
| | Made with weather resistant, UV resistant Centrex® polymer for durability and long life. |
| | Weatherproof, fixed face, Positive LCD display for easy viewing in direct sunlight. |
| | |
| Dimension | |
| | 54 1/4 H x 16 1/4 D x 26 5/8 W |
| | |
| weight | |
| | 107 lbs |
| | |
| | Operating Temp. -32°F ~ 104°F (0°C ~ 40°C) |
| | Storage Temp. -4°F ~ 140°F (-20°C ~ 60°C) |
| | Operating Humidity 0% ~ 90% Non-Condensing |
| | Storage Humidity 0% ~ 90% Non-Condensing |
| | |
| | Product specifications and design are subject to change without notice. |